DDC
Domestic Pumps





PUMP
The Dayliff DDC centrifugal non self priming closed impeller pump is specially designed for all small scale domestic and commercial water supply uses and is particularly suited for water boosting and transfer applications. The pump body is cast iron and the impeller brass.

DDC158 Econo is of lighter construction and is fitted with stainless steel impeller.

MOTOR
Pumps are close coupled to reliable TEFC electric motors designed for continuous operation and are provided with a thermal cut out to protect against electrical overload. They can be connected directly to the mains power supply through a 10A fuse or MCB.

Enclosure Class: IP44 ***Insulation Class:*** F ***Voltage:*** 1x240V ***Speed:*** 2900rpm

OPERATING CONDITIONS
Pumped Liquid: Thin, clean, chemically non-aggressive liquids without solid particles or fibres
Max. Fluid Temperature: +60°C
Max. Ambient Temperature: +40°C
Max. Suction Lift: 7m at sea level

PUMP DATA

Model	Motor		Current (A)	Dimensions (mm)					Weight (kg)
	kW	HP		L	W	H	DN1(")	DN2(")	
DDC 158E	0.75	1	4.5	305	190	240	1	1	12
DDC 158			5.2	305	190	260			14
DDC 170	1.1	1.5	7	346	230	293	1.5	1.5	21



P&S DAVIS & SHIRTLIFF