




PUMP

The Daylife DIX range of pumps are of non self-priming vertical multistage in-line centrifugal design incorporating inverter controllers suitable for a wide range of water supply, irrigation, liquid transfer and pressure boosting applications. The pumps are of heavy-duty construction designed for continuous duty in commercial and industrial applications and are quiet in operation. Pumps feature AISI 316 stainless steel for all hydraulic components in contact with water and are water lubricated with a standard cartridge type mechanical seal. They are supplied complete with BSP internally threaded counter flanges. Particular features include:-

- Integrated pressure set variable frequency inverter drive regulated by system demand that minimises energy consumption, reduces mechanical load and reduces operating cost
- Smart touch screen providing visual presentation of operating data, fault indication and set-up options
- In-built pump protection including high and low voltage, phase failure, overcurrent and motor overload, dry running and low flow cutoff with operator permission setting.
- Supplied with a pressure sensor to monitor and maintain pump's output at set constant pressure point
- Can be installed individually or with up to 4 no pumps connected in parallel for Booster set applications
- Automatic pump alternation in multi-pump booster systems to ensure automatic and uniform master to slave transfer and continuous operation in the event of pump failure
- Digital connectivity interface for BMS applications (Modbus RS485 communication port)

MOTOR

Pumps are coupled to IE5 permanent magnet variable high-speed motors complying with IEC standards and giving exceptional operating efficiency. The integral controller provides for soft start eliminating water hammer and other protection features enabling the motor to be directly connected to the mains power supply through an appropriately sized Fuse or MCB. This gives high levels of motor protection for long life and saves the cost of a supplementary motor control panel.

Enclosure Class: IP55

Insulation Class: F

Voltage: 3X415V

Speed: 3500rpm

OPERATING CONDITIONS

Pumped Liquids: Thin, clean, non-aggressive and non-explosive liquids without solid particles or fibres.

Liquid Temperature Range: -15°C to 105°C

Maximum Ambient Temperature: +40°C

Maximum Suction Lift: According to the NPSH curve plus a safety margin of 1m

Maximum Inlet Pressure: 6Bar.

PUMP DATA

Model	Power		Nominal Current (A)	Dimensions				Weight (kg)
	kW	HP		B1	B2	D1	D2	
DIX10/3	3	4	5.4	405	300	210	130	50
DIX10/4	4	5.5	7.2	435	420	270	160	56
DIX10/6	5.5	7.5	9.8	515	420	270	160	61
DIX10/8	7.5	10	13.3	575	420	270	160	69

