



### PUMP

Pedrollo 6SR44 submersible pumps are specifically designed for supply from boreholes, though can also be used in other submersible applications in either vertical or horizontal configuration. They feature a hydraulic design that incorporates floating impellers which together with especially resistant component materials provide high resistance to sand content in the pumped water.

The pump impellers and diffusers are made from technopolymer while the stage casings, top housing, suction connector, pump sleeve and shaft are made of AISI 304 stainless steel. The pump is supplied with a 4m tail cable.

### MOTOR

Pumps are coupled to a two pole sealed motor constructed principally from stainless steel. Motors require a remote direct in-line starter and if irregular electrical supply is prevalent an additional quick tripping multi function protection relay is recommended.

**Enclosure Class :** IP68      **Insulation Class :** F      **Speed:** 2900rpm      **Voltage:** 3x415V

### OPERATING CONDITIONS

**Pumped Liquid:** Thin, clean, chemically non aggressive liquids with a maximum sand content of 100gm/m<sup>3</sup>.

**Max. Liquid Temperature:** +35°C

**Max. Immersion Depth:** 200m

**Min. Borehole Diameter:** 153mm

### PUMP DATA

Model	Motor		Current (A) 3x415V	DN (")	Dimensions(mm)		Weight (Kg)
	kW	HP			H1	H2	
6SR44/8	9.2	12.5	22	3	1154	700	72
6SR44/10	11	15	24		1351	765	82
6SR44/12	15	20	32		1548	820	91
6SR44/14	15	20	32		1745	820	95
6SR44/16	18.5	25	39		1942	883	107
6SR44/20	22	30	47		2335	953	120
6SR44/25	30	40	64		2827	1098	144

