



PUMP

The GRUNDFOS SQ range of compact submersible borehole pumps are suitable for both continuous and intermittent operation in a wide variety of applications. These include domestic water supply, water transfer and irrigation duties from both boreholes and tanks and due to excellent starting characteristics, they are particularly suited to pressure control operation. The pumps offer a number of unique features provided by the built-in GRUNDFOS electronic motor controller including:-

- Run dry protection - no electrodes required
- Soft start design avoiding high electrical loads and water hammer - also ideal for generator operation
- Over and under voltage protection - ideal for unstable power conditions
- Overload and high temperature protection
- Excellent wear characteristics - can handle slightly silted waters
- 3" diameter to fit narrow boreholes.

Hydraulic components are made from polyamide plastic and the special design floating impellers each have a tungsten carbide/ceramic bearing. The pump sleeve, shaft and other principal components are made from stainless steel.

MOTOR

The unique integrated GRUNDFOS MS3 high efficiency permanent magnet motor is controlled by a built in frequency converter which increases the standard mains frequency enabling the pump to run at high speed. All control functions are built into the frequency converter and no additional motor protection is required other than a 13amps fuse or MCB.

Voltage: 1 x 240V

Speed: 10,700rpm

Power Factor: 1

OPERATING CONDITIONS

Pump liquid: Thin, clean, non aggressive liquids containing no solids or fibres.

Max. Water Temperature: +30°C (no liquid flow past motor)
+40°C (min 0.15 l/sec liquid flow past motor)

Max Water depth: 150m

Min Borehole Diameter: 80mm

PUMP DATA

Pump Type	Number of Stages	Power (kW)	Running Current (A)	Dimensions (mm)		Weight (kg)
				A	B	
SQ 2-35	2	0.7	5.2	741	265	5
SQ 2-85	5	1.2	8.4	825	346	6
SQ 2-115	7	1.9	12.3	889	373	7
SQ 3-30	2	0.7	5.2	745	265	5
SQ 3-65	5	1.2	8.4	825	346	5
SQ 3-105	8	1.9	12.3	942	427	7
SQ 5-25	2	0.7	5.2	743	265	6
SQ 5-50	4	1.7	11.2	824	346	7
SQ 5-70	6	1.9	12.3	941	427	7
SQ 7-30	2	1.2	8.4	743	265	6
SQ 7-40	3	1.7	11.2	862	346	7

